

TOP CLEAN TREND® XL 22 GREEN MOTION

Eco-Friendly Ribbed Carpet




We place a major emphasis on sustainability in our products. One example is the eco-friendly GREEN MOTION variant within the Top Clean system. All components are 100% recyclable and can be returned for re-use – free of charge. The eco-anodized profile with ribbed carpet is corrosion-resistant, has sound insulation, is easy to clean and rollable. The GREEN MOTION system is available in any width and length; special shapes are available on request.

- For use indoors or in covered outdoor areas
- Accessible
- Recyclable
- Eco-anodized
- Rust-proof
- Non-PVC

- | | | |
|--|--|--|
| 1 Zone 1: Coarse Dirt Collecting Area | 2 Zone 2: Intermediate Zone for heavily frequented Entrance Areas | 3 Zone 3: Fine Dirt and Damp Dirt Collecting Area |
|--|--|--|

TECHNICAL DATA











Aluprofile	Warp resistant aluminium profile (alloy EN AW 6060, wall thickness up to 1.5 mm), eco-anodized E6/EV 1 Completely recyclable
Upper	Eco friendly Ribbed Carpet: Unmixed, non-latex, fire-resistant and durable polypropylene. UV-resistant. Completely recyclable
Underside	Non-PVC rubber profile with proven sound insulation for low-noise traffic. Completely recyclable
Connection	Stainless steel wire rope V2A Ø 3 mm Rust-proof. Completely recyclable
Lock	Threaded nipple with stainless steel screw (rust-proof). Completely recyclable
Profile spacing	5 mm. Spacers are made of weather-resistant non-PVC rubber. Completely recyclable
Profile width Ribbed Carpet	37 mm
Mat height	ca. 22 mm
Wall thickness	up to 1,5 mm
Weight / m²	14,0 kg
Max. profile length in one piece	300 cm
Max. weight in one piece	50 kg
Special shapes	Can be custom-made to your specifications (at an extra charge)
Mat division	Standard = as of a profile length of 300 cm or weight of 50 kg Mat divisions into a profile length and weight according to customer requirements are possible
Mat connectors	High-quality connecting elements made of V2A are mounted in the factory in the case of multiple-part mats



TOP CLEAN TREND® XL 22 GREEN MOTION

Eco-friendly Ribbed Carpet

PRODUCT INFORMATION

Traffic¹⁾  medium	Suitability for wheels²⁾  800 kg	Static load³⁾  5.000 kg	Load per wheel⁴⁾  220 kg
Dirt absorption  medium	Moisture absorption  high	Slip resistance  Ribbed Carpet R11	Fire behaviour  Eco-friendly Ribbed Carpet Cfl-s1
Warranty⁵⁾  10 years	Reach⁶⁾  REACH-compliant		
Suitability to cross over with	Wheelchair, Luggage trolley, Shopping trolley, Transport trolley, Lift trucks		
Areas of application⁷⁾	<ul style="list-style-type: none"> • Object areas • Public areas • Private areas 		

ACCESSORIES

(for an additional charge)	<ul style="list-style-type: none"> • Mat frame • Dirt collecting trays • T-bars (for all multiple-part Top Clean mats without connectors)
----------------------------	--

SERVICES

(on site, for an additional charge)	<ul style="list-style-type: none"> • Building site advice • Measurement using digital measuring device • Fitting and laying service • Disposal of used mats • Repairs/replacement of insert types following wear • Cleaning
-------------------------------------	---

Ribbed Carpet



140 Anthracite
Eco-friendly
Ribbed Carpet

Due to technical limitations colours are only approximate.

1) Normal: used on foot up to approx. 2,800 times, medium: approx. 2,800 times or more, strong: approx. 5,100 times or more per day.

2) Suitable for a customary lift truck (tandem rollers) up to the specified total weight.

3) The static load tests to establish the load-bearing capacity of our entrance mats have been performed on a testing machine able to conduct tests with a load of up to 100 t, using a 10 x 10 cm (=100 cm²) pressure vessel. Mats with Brush Strips or Scraper Bars are only suitable for wheeled items to a limited extent. It is vital to avoid accelerating, braking or manoeuvring on the mats!

4) The specified loads refer to a polyurethane wheel with a diameter of 85 mm and width of 100 mm. When investigating our entrance matting systems, we simulated the point load that is applied to the mat by a single roller. To obtain the overall load, this value can be multiplied by the number of rollers that the means of transportation has.

5) Production and material defect warranty. The warranty depends on the manner of application, installation, and regular cleaning and maintenance in accordance with the recommendations of GEGGUS. All warranties are subject to our Terms of Sale and Supply. These can be found on the Internet at www.geggus.de.

6) GEGGUS products do not contain, in a concentration of more than 0.1%, any substances that are currently considered to be of very high concern (SVHC) and that are included on the candidate list.

7) When assessing the requirements for a particular application, the performance features of the individual mat types should be taken into account.